

Directional Coupler 350 ~ 2700MHz

Application

- ▶ Applications of Radio frequency and Microwave systems.
- ▶ Industrial and sensing applications.
- ▶ Radio frequency mixing and filtering.
- ▶ High power processing, anti-interference test , etc.
- ▶ It supports a one-year standard warranty.

RF Characteristics

Part Number	Frequency Range (MHz)	Nominal Coupling(dB)	IL. (dB)	Directivity (dB)	VSWR	Connector Type
5o5522440035027005NK	350 ~2700	5±1.0	2.05	18	1.3	N Female
5o5522440035027006NK	350 ~2700	6±1.0	1.7	18	1.3	N Female
5o5522440035027007NK	350 ~2700	7±1.0	1.4	18	1.3	N Female
5o55224400350270010NK	350 ~2700	10±1.2	0.8	18	1.3	N Female
5o55224400350270015NK	350 ~2700	15±1.2	0.35	18	1.3	N Female
5o55224400350270020NK	350 ~2700	20±1.5	0.25	18	1.3	N Female
5o55224400350270020NK	350 ~2700	25±1.5	0.2	18	1.3	N Female
5o55224400350270030NK	350 ~2700	30±2.0	0.2	18	1.3	N Female
5o55224400350270040NK	350 ~2700	40±2.0	0.2	12	1.3	N Female

